

CONSTRUCTION / PALLET FORK

SPECIFICATIONS



PALLET

Class	Tine Adjustment Style	Frame Width	Frame Height	Maximum Tine Spacing	Minum Tine Spacing	Tine Size	Load Capacity @ 24" Load CTR	Round Bar Diameter
10	Manual	48"	26"	48"	12"	2" X 4"	8000 lbs.	CL3
20	Manual	60"	26"	60"	12"	2" X 4"	8000 lbs.	CL3
30-50	Manual	60"	26"	60"	15"	2" X 5"	10000 lbs.	CL4
60	Manual	100"	48"	96"	34"	2-1/2" X 6"	21400 lbs.	2-1/2"

CONSTRUCTION

Class	Tine Adjustment Style	Frame Width	Frame Height	Maximum Tine Spacing	Minum Tine Spacing	Tine Size	Load Capacity @ 24" Load CTR	Round Bar Diameter
10	Manual	63"	38"	60"	12"	2" X 4"	8400 lbs.	2"
	Hydraulic	63"	38"	60"	12"			
20	Manual	64"	48"	60"	15"	2-1/2" X 6"	21400 lbs.	2-3/4"
		100"	48"	96"	34"			
	Hydraulic	64"	48"	60"	18"	2-1/2" X 6"	21400 lbs.	2-3/4"
		100"	48"	96"	34"			
30-50	Manual	64"	48"	60"	15"	2-1/2" X 6"	21400 lbs.	2-3/4"
		100"	48"	96"	34"			
	Hydraulic	64"	48"	60"	18"	2-1/2" X 6"	21400 lbs.	2-3/4"
		100"	48"	96"	34"			
60	Manual	106"	55"	101"	37"	3" X 7"	34200 lbs.	3-1/2"
	Hydraulic	106"	55"	101"	37"			
70-80	Manual	106"	55"	101"	39"	3-1/2" X 8"	54600 lbs.	3-1/2"
	Hydraulic	106"	55"	101"	39"			
90	Manual	106"	55"	101"	39"	4" X 8"	67600 lbs.	3-1/2"
	Hydraulic	106"	55"	101"	39"			

SEVERE DUTY

Class	Tine Adjustment Style	Frame Width	Frame Height	Maximum Tine Spacing	Minum Tine Spacing	Tine Size	Load Capacity @ 24" Load CTR	Round Bar Diameter
30-50	Manual	64"	48"	60"	17"	3" X 7"	34200 lbs.	3-1/2"
	Manual	100"	48"	96"	36"			
60	Manual	106"	55"	101"	39"	3-1/2" X 8"	54600 lbs.	4"

LOADING PROFILE

Class	Tine Adjustment Style	Frame Width	Frame Height	Maximum Tine Spacing	Minum Tine Spacing	Tine Size	Load Capacity @ 24" Load CTR	Round Bar Diameter
20-30-50	Manual	64"	48"	60"	15"	2-1/2" X 6"	21400 lbs.	2-3/4"
	Manual	100"	48"	96"	34"			
60	Manual	106"	55"	101"	37"	3" X 7"	34200 lbs.	3-1/2"